is referenced. The second column is presented for information only and may not be all inclusive. More recent versions of these standards may be used with advance approval of the Administrator. Copies of these materials may be obtained from American National Standards Institute, 11 West 42nd St., 13th Floor, New York, NY 10036. The table follows:

Document number and name	40 CFR part 92 reference
ANSI B109.1–1992, Diaphragm Type Gas Displacment Meters.	§92.117

## §92.6 Regulatory structure.

This section provides an overview of the regulatory structure of this part.

- (a) The regulations of this part 92 are intended to control emissions from inuse locomotives. Because locomotive chassis and locomotive engines are sometimes manufactured or remanufactured separately, the regulations in this part include some provisions that apply specifically to locomotive engines. However, the use of the term "locomotive engine" in the regulations in this part does not limit in any manner the liability of any manufacturer or remanufacturer for the emission performance of a locomotive powered by an engine that it has manufactured or remanufactured.
- (b) The locomotives and locomotive engines for which the regulations of this part (i.e., 40 CFR part 92) apply are specified by \$92.1, and by the definitions of \$92.2. The point at which a locomotive or locomotive engine becomes subject to the regulations of this part is determined by the definition of "new locomotive or new locomotive engine" in \$92.2. Subpart J of this part contains provisions exempting certain locomotives or locomotive engines from the regulations in this part under special circumstances.
- (c) To comply with the requirements of this part, a manufacturer or remanufacturer must demonstrate to EPA that the locomotive or locomotive engine meets the applicable standards of §§ 92.7 and 92.8, and all other requirements of this part. The requirements of this certification process are described in subparts C and D of this part.

- (d) Subpart B of this part specifies procedures and equipment to be used for conducting emission tests for the purpose of the regulations of this part.
- (e) Subparts E, F, G, and H of this part specify requirements for manufacturers and remanufacturers after certification; that is during production and use of the locomotives and locomotive engines.
- (f) Subpart I of this part contains requirements applicable to the importation of locomotives and locomotive engines.
- (g) Subpart K of this part contains requirements applicable to the owners and operators of locomotives and locomotive engines.
- (h) Subpart L of this part describes prohibited acts and contains other enforcement provisions relating to locomotives and locomotive engines.
- (i) Unless specified otherwise, the provisions of this part apply to all locomotives and locomotive engines subject to the emission standards of this part.

## §92.7 General standards.

- (a) Locomotives and locomotive engines may not be equipped with defeat devices.
- (b) New locomotives fueled with a volatile fuel shall be designed to minimize evaporative emissions during normal operation, including periods when the engine is shut down.
- (c)(1) Locomotive hardware for refueling locomotives fueled with a volatile fuel shall be designed so as to minimize the escape of fuel vapors.
- (2) Hoses used to refuel gaseousfueled locomotives shall not be designed to be bled or vented to the atmosphere under normal operating conditions.
- (3) No valves or pressure relief vents shall be used on gaseous-fueled locomotives except as emergency safety devices, and these shall not operate at normal system operating flows and pressures.
- (d) All new locomotives and new locomotive engines subject to any of the standards imposed by this subpart shall, prior to sale, introduction into